

HG tile protector (product 14)

- adds a satin shine

HG tile protector is an easily applicable liquid polymer emulsion for all types of floor tiles, flagstones and slate. When dry, this emulsion forms a glossy, super-thin yet extremely strong protective film, which protects tiles against stains, dirt, scratches and wear, while also enhancing the colour and structure. This protective film also gives an anti-slip effect.

Directions:

1. The base must be completely clean and free of grease and dust. For the treatments that may be required: see the HG floor tiles treating matrix on the side of this bottle.
2. The glue/cement and grouting of new floors must be completely hardened and dry. The drying time is usually 4-6 weeks.
3. Existing, porous floors must be well dried after cleaning. The underfloor heating must be switched off for at least 12 hours prior to the treatment with this product.
4. Treat porous floors beforehand with *HG tile impregnating protector (product 13)*.
5. Do not shake before use and preferably apply with a wax applicator (see the picture on the front of this bottle). It is also possible to use a lint-free, clean (tea)towel wrapped around a squeegee. Use a paint roller (fur roller) on a coarse base.
6. Pour the liquid onto the floor and spread it in straight tracks in one direction. Do not turn or rub.
7. Once the product has dried (after about 40 minutes), a second layer can be applied crosswise onto the first layer.
8. The floor can be walked on about 3 hours after the final treatment and has completely hardened after 3 days.

Coverage: ± 40 m² per litre per layer.

Maintenance:

For regular mopping: *HG tile cleaner shine restorer (product 17)*. See also the HG floor tile treating matrix on the side of this bottle.

Tip: For regular maintenance of the protective film we advise mopping the floor once a month with a solution of 50 ml (half a cup) in half a bucket (5L) of water.

In walkways where the protective film is more liable to wear, a new protective film can be quickly and easily applied over the existing layer, when necessary. In such cases, first clean the floor using *HG tile cleaner extra strong (product 20)*, see also the HG floor tiles treating matrix on the side of this bottle.

Attention: This product should be used indoors only, but not in rooms that can be wet, such as bathrooms. For calciferous natural stone: see our HG natural stone line.