



A008 : SELSEAL

acrylic base coat seal

Description of product

Non-yellowing polymer film. Does not discolour even the lightest floor. Penetrates and seals porous floors, provides an ideal base for emulsion application. Resistant to polish strippers.

Product Uses


For all linoleum, P.V.C., rubber, terrazzo and thermoplastic floors. N.B. Do not use on unsealed wood and cork floor coverings.

Directions

Selseal must be applied to a clean grease free floor. Apply a thin even film of seal using a clean lint free mop or applicator. Apply a second coat when the first is dry (approximately 30 mins). COVERAGE: 50 square metres per litre. MAINTENANCE: Selseal is formulated as a sealer coat and does not have a high resistance to wear. It must be finished by the application of Selexel or other metallised polymer emulsion and normal maintenance techniques employed. PROTECT FROM FROST. FOR PROFESSIONAL USE ONLY.

iN Insight Supported

iN Insight is Selden's interactive product selection and training system. Enables the user to create full COSHH training kits, wallcharts, task cards and more. visit <http://www.selden.co.uk/insight>




iN Insight recommended product uses

Flooring - pre-sealing (semi permanent)

typical dilution
neat

Product Hazards and PPE Requirements



Risk Phrases
NC Not classified.

Safety Phrases
S2 Keep out of the reach of children., P13 Safety data sheet available for professional user on request.

Technical Data

| | |
|-------------|---|
| Composition | A blend of acrylic copolymers, resins incorporating wetting agents and film forming aids in a stable water based emulsion |
| Appearance | Translucent emulsion |
| Colour | Cream |
| Viscosity | <10 cps |
| Density | 1.012 |
| pH | 9.2 |
| Activity | 16% |
| Fragrance | Characteristic slightly sweet |
| Stability | 2 years in a unopened container |
| Storage | Protect from freezing |

Environmental Profile

Biodegradability
All surfactants contained in Selden Products meet the requirements of the EU Detergent Directive 2005 – 2004/648/EC. This requires all surfactants to break down both quickly and completely into harmless material such as CO2 and water.

Selden Environmental Charter


- We set ourselves industry leading standards.
- Selden minimises wastage, packaging and transportation.
- If it can be recycled, it will be recycled.
- Our chemicals policy exceeds regulatory requirements.
- We don't expect other people to clean up after us.
- Conserving energy, preserving resources.
- By being innovative, we strive to do better.
- We like to work in partnership with our clients.

Visit our website for more information.

External Accreditations

- 9001 - Quality System
- 14001 - Environmental System
- 18001 - Health & Safety System
- IPPC Certified Manufacturer

Sustainability
Product conforms with the DEFRA endorsed Sustainable Cleaning guidance



COSHH+ Supported

Selden's bespoke COSHH awareness and product training tool. Users specify the products in use and instantly generate a full training pack to enable quick and effective staff training.



www.flagship-mcp.com

Flagship products are those products that are included in Selden Multi-language Cleaning Programme. Flagship products have induction kits, best practise guidance, MSDS, wallcharts and usage guides available in the following languages

- english, french, spanish, portuguese, polish, german, dutch, russian, romanian, estonian, czech, croatian.




ISO 9001



ISO 14001



ISO 18001

UKAS
accredited testing
laboratory No. 4204



SELLEN
formulating
testing
manufacturing
to
the highest
standards

Selden Research Limited

Staden Business Park, Staden Lane, Buxton
Derbyshire. SK17 9RZ

Tel : 01298 26226 | Fax : 01298 26540 | Email : info@selden.co.uk | web : www.selden.co.uk

